




ESF/A9

Solar Flood Light




Product advantages and features

- Supplied with solar panel
- Integrated with LiFePO4 battery
- ABS housing, tempered glass, aluminum reflector
- SMD5050 LED





Model	Solar Panel	Battery	CCT	Lumen	BA
ESF/A9	5V/25W	3.2V/25Ah LiFePO4	3000K	2200lm	75°

Dimension



Photometric curves



Lighting mode

- Charging time with solar irradiation is 5-8 hours.
- Basic light mode is shown on the right.
- Another mode is brightness adjustment mode, which is indicated on remote control.
- Best effect, recommended use of "AUTO" automatic mode.
- Usually power on (installed) is defaulted to automatic mode.
- Automatic mode: The brightness of the whole lamp can be adaptively controlled according to the battery's own power.

Brightness	AUTO	3H	5H	8H
Initial	100%	100%	100%	100%
Decrease Progressively				
0.5H	70%	70%	70%	70%
1st H	70%	70%	70%	70%
2nd H	70%	70%	70%	70%
3rd H	60%	60%	60%	60%
4th H	50%	OFF	50%	50%
5th H	50%		50%	50%
6th H	40%		OFF	40%
7th H	30%			30%
8th H	20%			OFF
9th H	20%			
10th H	20%			
11th H	60%			
12th H	60%			

How to use remote control

