



Shine\*R



Shine\*R-TL

# Shine\*R Shine\*R-TL

## SPOT LIGHT



### APPLICATIONS

- Hotel
- Villa
- Corridors
- Residential


### CONSTRUCTION

- Die-casting aluminum body and PC reflector
- ADC12 aluminum bezels
- Adjustable: Rotation 350°, tilt 0-30°
- Heatsink: Soft touch coating for a premium feel

### TECHNICAL DETAILS

- COB LED: SDCM<3
- With lens
- Flicker free LED driver
- Rated life: 50,000 hours

### OPTIONAL ACCESSORIES




### OPTIONAL REFLECTORS




Model	Input	Power	CCT	Lumen	CRI	BA
Shine55R	220-240V	9W	2700K/3000K/3500K/4000K	710lm	>95	15°/24°/36°/60°
Shine55R-TL	220-240V	9W	2700K/3000K/3500K/4000K	710lm	>95	15°/24°/36°/60°
Shine75R	220-240V	15W	2700K/3000K/3500K/4000K	1120lm	>95	15°/24°/36°/60°
Shine75R-TL	220-240V	15W	2700K/3000K/3500K/4000K	1120lm	>95	15°/24°/36°/60°
Shine95R	220-240V	25W	2700K/3000K/3500K/4000K	1870lm	>95	15°/24°/36°/60°
Shine95R-TL	220-240V	25W	2700K/3000K/3500K/4000K	1870lm	>95	15°/24°/36°/60°


**PHOTOMETRIC CURVES**



Shine55R 9W



Shine75R 15W




Shine95R 25W




**Patent design, easy to maintenance**  
Specially designed string hidden inside,  
Easily pull out the led module when necessary.


**DIMENSION**




Shine55R




Shine55R-TL




Shine75R



Shine75R-TL



Shine95R



Shine95R-TL





**DIMENSION**

